

# Baugrößen

Asynchrongeneratoren in geschlossener Ausführung, Schutzart IP 54/44,  
mit Kugellager, Bauform B3 + Bauform B5

kVA	750 1/min	1000 1/min	1500 1/min	3000 1/min		
0,34	90S8	80K6	71G4	71K2		
0,5	90L8	80G6	80K4	71G2		
0,7	100L8	90S6	80G4	80K2		
1	100LX8	90L6	90S4	80G2		
1,4	112M8	100L6	90L4	90S2		
2	132S8	112M6	100L4	90L2		
2,7	132M8	132S6	100LX4	100L2		
3,5	160M8	132M6	112M4	112M2		
5	160MX8	132MX6	132S4	132S2		
7,0	160L8	160M6	160M4	132SX2		
10	180L8	160L6	160M4	160M2		
13	200L8	180L6	160L4	160MX2		
17	225S8	200L6	180M4	160L2		
20	225M8	200LX6	180L4	180M2		
27	250M8	225M6	200L4	200L2		
34	280S8	250M6	225S4	200LX2		
40	280M8	280S6	225M4	225M2		
50	315S8	280M6	250M4	250M2		
65	315M8	315S6	280S4	280S2		
80	315MX8	315M6	280M4	280M2		
95	315MY8	315MX6	315S4	315S2		
115	315L8	315MY6	315M4	315M2		
140	315LX8	315L6	315MX4	315MX2		
175	355M8	315LX6	315MY4	315MY2		
220	355MX8	355M6	315L4			
275		355MX6	315LX4			
310		355LY6	355M4			
Stand Dez. 2009						